

Status: 11/5/2025

# **Lizerna Protect Pro**

# Equipment and impregnating agents

#### **Properties**

- Air-permeable fabric impregnation
- stabilizes the fibres as a finishing agent
- PFAS free

#### **Application**

Lizerna Protect Pro can be used both as a finishing product and as an impregnating agent.

#### Impregnating agent

- 1. Preparing the textiles
- Textiles must always be rinsed to completely remove detergent and alkali residues.
- Even small residues can significantly impair the impregnation effect.

# 2. Adjusting the finishing bath

- pH value: 5-6
- If necessary, add acetic acid or formic acid to correct the pH.
- Lizerna Protect Pro is added to the finishing bath.

#### 3Impregnation

- The textiles are treated in the last rinse bath after the liquor level has been reached with the start of the drum movement.
- Treatment time: approx. 15 minutes (recommended for maximum impregnation effect).
- Heating the liquor to 30°C improves the absorption capacity.

#### 4. post-treatment

- After impregnation, the fabric is briefly spun and then dried.
- For membrane textiles: spin at several intervals.

# Textile finishing

Lizerna Protect Pro is an important finishing agent in the BÜFA Care 4.0 wet-cleaning process. The product is used in the final rinse bath, where it substantively coats the fibers. As a result, it forms a protective film on delicate fabrics such as wool, silk and viscose. This protection ensures that the fibers are protected in the subsequent drying process and that their structure, feel and elasticity are retained.



Status: 11/5/2025

### **Dosing**

Impregnating agent

Concentration 20 - 30 ml / I water

Temperature 20 - 40 °C Exposure time 20 - 30 min.

Addition depending on the desired effect and tissue type

**Textile finishing** 

Concentration 6 - 10 ml / kg dry wash

Temperature 30 - 50 °C

Addition As an additive in the final rinse bath

#### **Technical data**

Density (20°C)	pH-value
1,00 kg/l	4

#### **Notes**

Only store the product in its original container.

The product is sensitive to frost and heat and must not be stored at temperatures below 0 °C and above 40 °C.

Irreparable product damage is possible.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.