

SolventClean 50

High-boiling solvent cleaner

Properties

- Particularly suitable for removing pigment powders
- distillable
- Flash point according to DIN EN 22719-A: >77 °C

Application

SolventClean 50 is a high-boiling solvent cleaner for direct use in manual cleaning or immersion applications. SolventClean 50 is low foaming and designed for the removal of pigment powders. The cleaner dries quickly and residue-free.

Instructions for use:

Increased residual adhesion of SolventClean 50 can be removed by rubbing with cotton or fleece cloths. Rinsing with water is also possible if the application permits.

Suitable surfaces: Steel, stainless steel, aluminium, aluminium alloys, galvanized material, non-ferrous metals

Only treat after testing: Plastics

Area of application: manual process and immersion process

For removing: primarily pigment powders

Technical data

Density (20°C)

0,80 kg / l

Notes

Only store the product in the original container, tightly closed and dry. After removing partial quantities, please close the container tightly again. Protect from direct sunlight. Do not inhale aerosols, use only in a well-ventilated area.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.