

BÜFA-Floc

Flocculants for waste water treatment

Properties

- Highly active, therefore very economical to use
- Suitable for manual and automatic dosing
- Binds even the smallest dirt particles
- does not contain any organic components

Application

BÜFA-Floc is used as a (primary) flocculant for water and waste water treatment. BÜFA-Floc is particularly suitable for use in vehicle washing systems with integrated water treatment. By using BÜFA-Floc, even the smallest suspended particles and dirt part

Dosing

Automatic dosing

| | |
|----------|---|
| Addition | The dosing system manufacturer's specifications must be observed. |
|----------|---|

Manual dosing

| | |
|---------------|--|
| Concentration | 1 - 3 ml / m ³ |
| Addition | Addition via pre-filter, expansion tank, fiber catcher, overflow channel, etc. |

Technical data

| Density (20°C) | pH-value |
|----------------|-----------|
| 1,04 | 4,2 - 4,8 |

Notes

Only store the product in the original container and in a frost-free place.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

The product does not contain any organic complexing agents that are not sufficiently biodegradable, such as EDTA (in accordance with Annex 49 of the Waste Water Ordinance).

Due to the formulation components used, no organically bound halogen compounds (AOX) are contained as active substances.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.