


Lavenium FP

Carpet foam cleaner

Properties

- cleans carpets, rugs, upholstered furniture, car upholstery, etc.
- reduces resoiling and has an antistatic effect
- suitable for all standard shampooing devices
- gives the treated textiles a silky shine



Application

1 part Lavenium FP and 8 - 15 parts of water as a shampoo solution. The dilution depends on the degree of soiling. Thoroughly vacuum the carpet or upholstery before treatment. A hem test is required for color-sensitive articles.

Carpet care

The carpet surface to be cleaned is evenly foamed with a suitable shampooing device. After a residence time of approx. 10 minutes, the foam can be removed with a wet vacuum cleaner to speed up the drying process. The cleaning process is completed by thoroughly vacuuming the dry, solid product residue with the trapped dirt.

Upholstery treatment

When cleaning upholstery, dry foam (dilution 1:8) should be used if possible so that the material does not become too wet. The parts to be treated are lathered with a special hand sprayer. To improve the depth effect, massage the foam into the upholstery using a coarse sponge. After drying, the crystalline, dirt-laden Lavenium FP residue is removed with a high-performance vacuum cleaner. This cleaning process describes a fibre-friendly, effective and at the same time practical and economical method for cleaning firmly processed upholstery fabrics.

Technical data

Density (20°C)	pH-value
1,02 kg / l	7,0 - 8,0

Notes

Store the product in its original container.

The storage area should be frost-free, although solidified products can be reused without loss of quality after thawing.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.