

Petrosol Flüssig

Strongly acidic water and scale cleaner

Properties

- Dissolves water scale incrustations and deposits
- Thoroughly removes scale
- foam-free
- with corrosion protection

Application

Petrosol Flüssig is an inorganic acid with special corrosion inhibitors and is used to remove water scale incrustations and hardness deposits in hot water boilers, pipes, containers, jug and bottle washers, etc. The amount of Petrosol Flüssig required for de gas development stops and the solution is only slightly acidic or neutral, the Petrosol Flüssig has been used up. In this case, some of the solution is drained off and product is added. If the solution is still strongly acidic after the gas stops develop

Dosing

Decalcification

Addition	Submit water
----------	--------------

Technical data

Density (20°C)	pH-value
1,14	1,25 ; 1 %

Notes

Store the product only in the original container and frost-free.
Direct sunlight should be avoided.
After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.