

RHE Forte

Smoke resin remover



Properties

- strong alkaline foam cleaner
- thorough removal of persistent grease and protein residues
- good dirt-breaking properties
- highly active wetting agents

Application

RHE Forte is a highly alkaline foam cleaner for removing persistent encrusted soiling. Thanks to its content of grease-dissolving, emulsifying surfactants and complexing agents, it is ideal for use on difficult-to-remove grease, protein and smoke resin soiling. RHE Forte can be used on all alkali-insensitive surfaces. The product is suitable for cleaning measures in meat, fish and delicatessen processing.

For other cleaning tasks, RHE Forte can also be used manually or in a bath process (e.g. for boiling). After cleaning, it is essential to rinse with water of drinking water quality until it is alkali-free.

Dosing

Smoke resin removal

Concentration	2,0 - 5,0 %
Temperature	50 - 90 °C
Exposure time	20 - 40 min.
Addition	After cleaning with RHE Forte, rinse with drinking water quality.

Technical data

Density (20°C)	pH-value	Conductance (1%; 20°C)
1,30 kg / l	12,55 ; 1 %	14,35 mS/cm

Titration

Prepare 10 ml application solution and titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.

Consumption (ml) x 0.15 = concentration in %

Notes

Storage:

Store the product only in the original container and in a frost-free place between +5 and +40°C. Avoid direct sunlight. After removing partial quantities, please reseal the container tightly.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.