

BÜFA TDC 2000

Hydrocarbon solvent



Properties

- Long-term stabilized by addition
- Low odor threshold value
- is characterized by a very narrow fractional cut
- fulfills the requirements of 31. BImSchV Annex III Point 3.1.2 c)

Application

BÜFA TDC 2000 is a high-purity isoparaffinic solvent specially developed to meet the needs of textile care.

BÜFA TDC 2000 is characterized by a very narrow fraction cut and consists almost exclusively of a mixture of isomers with a chain length of C11 - C12. Low, strong-smelling hydrocarbon components (C9 - C10), which reduce the flash point and the lower explosion limit, and high hydrocarbon components (C13 - C15), which extend the drying time and thus the batch duration, are practically non-existent. This makes the odorless BÜFA TDC 2000 with a flash point of over 60°C and a favorable evaporation rate a future-oriented solvent for textile care. It has also been stabilized for the long term using special additives.

This is a product from the KWL textile cleaning range.

Boiling range (1013 mbar)

Start: 180°C

End: 200°C

Flash point: >61°C

Water solubility: <20 mg/l

Evaporation rate (diethyl ether = 1): approx. 115

Vapor pressure (20°C): approx. 0.77 g/ml

Total aromatic content: <100 mg/kg

Benzene content: <1 mg/kg

Halogen content (chlorine): <5 mg/kg

Calculation index: 1.426

Kauri Butanol Index: approx. 27

Technical data

| Density (20°C) |
|----------------|
| 0,77 kg / l |

Notes

Only store the product in the original container, tightly closed, in a cool and dry place.
Protect from direct sunlight.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.