Status: 11/13/2026

SolventClean QuickDry

Quick-drying Solventbased Cleaner

Properties

- Quick drying
- For removing solvent-based inks, even when dry; also suitable for cross-linked, water-based inks and UV inks

Application

SolventClean QuickDry is a quick-drying solvent cleaner for direct use in manual cleaning. SolventClean QuickDry is designed for the removal of paints and varnishes.

Suitable surfaces: steel, stainless steel
Only treat after testing: Aluminium, aluminium alloys, galvanized material, non-ferrous metals, plastics
Area of application: manual process
For removal of: all paint systems

Dosing

Manual procedures	
Concentration	100 %
Temperature	15 °C – 25 °C

Technical data

Density (20°C)
0,87 kg / l

Notes

Only store the product in the original container, tightly closed, in a cool and dry place. After removing partial quantities, please close the container tightly again. Protect from direct sunlight. Do not inhale aerosols, use only in a well-ventilated area.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.

BÜFA Cleaning GmbH & Co. KG · August-Hanken-Str. 30 · 26125 Oldenburg · GERMANY
Phone +49 441 9317-251 · cleaning@buefa.de · www.buefa-cleaning.com