


# Oldomat Pulver

## Diswashing powder



### Properties

- chlorine containing
- phosphate containing
- alkaline
- for all degrees of water hardnesses

### Application

Oldomat powder is an alkaline, low-foaming machine rinse aid. Due to the proportion of hardness stabilizers and inhibitors, it can be used both in service water with low water hardness and in water with a higher degree of hardness. The combination of alkali silicate structure and highly effective surfactants ensures rapid wetting and gentle cleaning of the dishes with excellent grease and dirt dissolving properties. An additional proportion of stabilized organic chlorine compounds ensures hygienic cleanliness and removes problem soiling as well as coffee and tea residues. Oldomat powder is suitable for use in all commercial and domestic dishwashers. Dosing is possible using appropriate powder dosing systems or manual dosing. If added manually, the Oldomat powder is poured directly into the machine or the dosing device provided for this purpose before cleaning begins. If added manually, the Oldomat powder product is added directly to the machine or the dosing device provided for this purpose before cleaning begins.

Hardness range\*/water hardness\*/dosing  
1 / 0 - 7°dH / 1.5 g per liter  
2 / 7 - 14°dH / 2.0 g per liter  
3 / 14 - 21°dH / 3.0 g per liter

\*You can find out the hardness range or water hardness in °dH from your local waterworks.

After treatment with cleaning products, rinse with fresh water when used in food processing plants to remove all product residues from the cleaned surface. The use of our Oldomat Klar rinse aid ensures a drip-free surface.

### Technical data

pH-value	Bulk weight
12,0 ; 1 %	ca. 900 kg / m <sup>3</sup>

### Titration

Prepare 10 ml application solution, fill up with approx. 100 ml distilled water and add a spatula tip of sodium thiosulphate. Titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.

Consumption (ml) x 0.25 = concentration in %

### Notes

**Storage:**

Store the product only in the original container and frost-free.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.