Status: 11/17/2026

Benzapon Sanofresh

Cleaning booster

F

Properties

- optimum cleaning effect
- prevents graying and has a high water-binding capacity
- can also be used for brushing
- good antistatic effect

Application

Master batch
2 - 3 ml Benzapon Sanofresh per liter of solvent in the working tank and filter

Follow-up
Machines without distillation Daily addition at the start of work (10 batches/day) = 1 ml Benzapon Sanofresh per liter of solvent in tanks and filters

1-Bath process
Spin proportion for distillation (25% liquor exchange) or distillation of the entire contents of the working tank after 10 batches at the latest = 3 - 5 ml Benzapon Sanofresh / kg goods (0,3 - 0.5 vol.-%).
For intensive pre-spotting with Benzapon Pre, the lower value should be used as a guide.

2-bath process
Fleet regeneration by distillation of the entire 1st bath (approx. 50%) = 10 ml Benzapon Sanofresh / kg fabric (1 vol.-%) in the 2nd bath

Use as a brushing agent
If Benzapon Sanofresh is used for brushing, it should be diluted 1:1 to 1:5 with KWL.

Technical data

Density (20°C)	pH-value
0,90 kg / l	7,5

Notes

Store the product in a frost-free location. Although the products may solidify, they can be used again after thawing without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.

BÜFA Cleaning GmbH & Co. KG · August-Hanken-Str. 30 · 26125 Oldenburg · GERMANY
Phone +49 441 9317-251 · cleaning@buefa.de · www.buefa-cleaning.com