

# Devantol Super

## Brushing agent



### Properties

- is easy to dose and can be mixed with water in any ratio
- Easy to rinse out and leaves no graying on the brushing areas
- Excellent for heavily soiled goods as an additive to the pre-cleaning bath

### Application

Devantol Super is a medium viscosity, almost colorless liquid that smells pleasantly fresh. Thanks to the selected surfactants and ingredients, it can be mixed with water in any ratio. For spraying with steam, Devantol Super is added undiluted to the reservoir of the spraying table. When spraying a Devantol Super solution, ensure that there is sufficient suction to avoid inhalation of aerosols. When pre-spraying with Devantol Super, a sufficient base concentration of cleaning booster is necessary to avoid graying. Take care when using on sensitive goods. If in doubt (especially if colour fastness is suspected), carry out a hem test.

As a cleaner for the rear wall of the drum

To clean the rear wall of the drum and the piping, the needle trap is cleaned the day before and the distillation still is distilled empty and cooled overnight. The next day, the cold distillation bubble is cleaned and not switched on! It may be used for No fabric may be placed in the drum for cleaning! The amount of solvent required for the cleaning process is determined first. As much solvent should be pumped into the drum until the solvent is almost 10 cm high in the drum. The required product quantities refer to the solvent volume determined in this process. If the volume is determined for the first time, the solvent must then be pumped back into the tank and the drum dried. Before the required amount of solvent is pumped into the drum, 0.6 liters of Devantol Super and 1.5 liters of water are added to the empty drum per 100 liters. To this mixture, the solvent from the clean tank is pumped into the stationary drum (if available by means of backflushing). Reverse cleaning is then carried out in the pump circuit (without filter) for 10 minutes. The machine is then spun in a stationary bath. After reaching the maximum rotation, the machine spins for 10 seconds. Depending on the degree of soiling, these two steps (reverse cleaning and spinning in the bath) must be repeated several times. The solvent is then pumped into the switched-off distillation unit. Further solvent (about half the amount previously used) is then pumped from the working tank into the drum and cleaned in the pump circuit for 5 minutes. This solvent is also pumped into the switched-off distillation unit. Finally, solvent is pumped directly from the working tank into the distillation unit for about 10 seconds. The drum can now be dried. After the last solvent has been pumped into the distillation unit, the distillation unit is switched on. To avoid boiling over, it may be necessary to regulate the temperature of the distillation, e.g. by means of a steam shut-off valve. After the distillation is finished, it should be cleaned before the next cleaning batch.

### Dosing

#### Spraying without steam

Concentration	1 : 1 - 1 : 3 in proportion with water
Exposure time	10 - 15 min.
Addition	Then place in the dry cleaning machine

#### Brushing

Concentration	pure or 1 : 0.5 - 1 : 3 in proportion with water
Exposure time	10 - 15 min.
Addition	Then place in the dry cleaning machine

### Technical data

Density (20°C)	pH-value
1,00 kg / l	8

### Notes

Only store the product in its original container and in a frost-free place.  
The product is not sensitive to frost, but becomes viscous and can even solidify if stored below 0 °C for longer periods. After warming up, however, it can be used again without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.