


Selekta PL 100

Alkaline basic cleaner

Properties

- Removes extreme soiling quickly and powerfully
- Particularly oily and greasy incrustations
- for manual and machine applications
- Can be used with all common HD/HW devices



Application

Selekta PL 100 is used as an alkaline cleaner for the basic and maintenance cleaning of engines, machines, commercial vehicles, truck tarpaulins, plastics and also for industrial cleaning. The product is used as a cleaner in high-pressure equipment, for mSelekta PL 100 can be mixed with water in any ratio. The application concentration depends on the degree of soiling of the surfaces and parts to be cleaned. If pre-dilution is required for automatic dosing, follow the instructions of the appliance manufacturer. After cleaning, rinse thoroughly with clean water to remove all detergent residues and loosened dirt. When using for the first time, carry out a test application in a concealed area to check the compatibility of the material.

The product can also be used via HD/HW devices with an application concentrate of 0.15 - 1.0 % (at the nozzle).

Dosing

Maintenance cleaning

Concentration	1:20 to 1:50 in proportion with water
---------------	---------------------------------------

Technical data

Density (20°C)	pH-value
1,05 kg / l	11,4 ; 1 %

Notes

Only store the product in the original container and in a frost-free place.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

The surfactants contained in the product meet the conditions regarding biodegradability as specified in Regulation EC 648/2004 for detergents.

The product does not contain any organic complexing agents that are not sufficiently biodegradable, e.g. EDTA (according to Annex 49 of the Waste Water Ordinance).

Due to the formulation components used, no organically bound halogen compounds (AOX) are contained as active substances.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.