

SECASENE Neo Boost

Cleaning booster



Properties

- specially adapted to the properties of SENSENE™ Neo
- low-foaming formulation; can also be used for small distillations
- significantly improved dirt removal thanks to optimized surfactant mixture

Application

1-bath process

Spinning portion for distillation (approx. 25 % liquor exchange) = 2 - 3 ml SECASENE™ Neo Boost / kg fabric

2-bath process

Liquor regeneration by distillation of the entire 1st bath (50 % liquor exchange) = 8 - 10 ml SECASENE™ Neo Boost/ kg fabric in the 2nd bath

Dosing

Master record

Concentration	1 - 2 %
Addition	in the working tank and filter

Postscript

Concentration	0,8 - 1,0 %
---------------	-------------

Technical data

Density (20°C)	pH-value
0,95 kg / l	7

Notes

Only store the product in its original container and in a frost-free place.

The product is not sensitive to frost, but becomes viscous if stored below 0 °C for longer periods. After warming up, however, it can be used again without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.