

Complement Thix P

Additive for thixotroping aqueous alkaline cleaners

Properties

- Individual consistency setting for the application of layer thicknesses from 200 µm to 800 µm
- Removes paint incrustations and cross-linked paint adhesions in permanently installed containers
- for application to vertical surfaces to build up a stable cleaning layer
- ensures that the strong cleaning power of a Paintex cleaning solution can fully develop its effect on vertical surfaces

Application

Complement Thix P is a thixotropic agent specially developed for the Paintex cleaners Paintex 1998, Paintex 839 and Paintex 2020. Complement Thix P leads to a thixotropic consistency. This builds up a stable cleaning layer on vertical surfaces and greatly extends the contact time. In particular, the cleaning of permanently installed containers and storage tanks at ambient temperature is greatly facilitated. The thixotropy can be adjusted over a wide temperature range with an addition of 1 vol% to 1.5 vol% in the cleaning mixture. The soiling is dissolved and / or infiltrated and can be easily rinsed off with water and pressure.

Attention! The order of addition must be strictly adhered to in order to obtain a cleaning mixture that is easy to apply. Observe a maturing time of approx. 10 minutes.

Process instructions:

1. Place any amount of Paintex in a suitable mixing container
2. Add COMPLEMENT THIX P 1 vol% - 2 vol% while stirring; homogenize well
3. Add 60-70% water while stirring vigorously (for solvent-based paint systems, add the same amount of water as Paintex)
4. Allow to mature for 10 minutes
5. Apply e.g. using the airless spray method (see <https://www.airless-technik.de>)

Shelf life of the thixotropic cleaner mixture: It is recommended to use the thixotropic cleaner mixture within one day. The thixotropic property is reduced after approx. 4 days. Suitable surfaces: Steel, stainless steel, HDPE, Teflon

Not suitable surfaces: Aluminum, zinc, non-ferrous metals and plastics

Area of application: Application on vertical surfaces to build up a stable cleaning layer

For the removal of: Paint encrustations and cross-linked paint adhesions of all paint systems

Technical data

pH-value	Bulk weight
6,0 - 8,5 ; 2 %	ca. 1,38 kg / m³

Notes

Store the product in its original container.

Storage should be frost-proof, although the solidified products can be used again after thawing without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.