

Tolo Aktiv

Grease remover, universally applicable



Properties

- Very effective
- Optimum cleaning results
- gentle on materials
- skin-friendly

Application

Tolo Aktiv is also suitable for cleaning and degreasing repair parts, metal surfaces and floors using high pressure, steam or spray equipment. The product is highly foaming and therefore not suitable for use in automatic dishwashers.

The Tolo AktivTolo Aktiv can be used with cold water, but the use of warm water significantly improves the cleaning result. For stubborn soiling (e.g. on extractor hoods), mixing with Tolo GFB Liquid has proven effective. We recommend mixing a 1:1:1 ratio of water : To

Dosing

Sprayers / Sprayers

Concentration	250 - 2.500 ml / 10 l water
Addition	max. 10 bar spray pressure

Technical data

Density (20°C)	pH-value
1,03	13,1

Notes

Store the product only in the original container and frost-free.
Direct sunlight should be avoided.
After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.