

Tolo Aktiv

Grease remover, universally applicable



Properties

- very effective
- for optimal cleaning results
- gentle on materials
- skin-friendly

Application

Tolo Aktiv is also suitable for cleaning and degreasing repair parts, metal surfaces and floors using high pressure, steam or spray equipment. The product is highly foaming and therefore not suitable for use in automatic dishwashers.

The Tolo Aktiv application solution is foamed onto the cold surface or applied with a brush or wet sponge. After a suitable contact time, wipe with a damp cloth or rinse thoroughly with water. Do not treat hot surfaces and do not allow to dry, especially on painted surfaces.

Tolo Aktiv can be used with cold water, but the use of warm water significantly improves the cleaning result. For stubborn soiling (e.g. on extractor hoods), mixing with Orbin GFB has proven effective. We recommend mixing a 1:1:1 ratio of water : Tolo Aktiv : Orbin GFB. For problematic soiling, Tolo Aktiv can also be used in a higher concentration.

If the products are applied via nozzles, misting must be avoided. Alkali-sensitive oil-based paints may change their appearance on contact with Tolo Aktiv. If in doubt about material resistance, carry out trial tests. After cleaning with Tolo Aktiv in food processing plants, rinse with fresh water to remove all product residues from the cleaned surface.

Dosing

Foam cleaning

Concentration	250 - 500 ml / 10 l water
---------------	---------------------------

Spraying application

Concentration	250ml - 2,5l / 10 l water
Addition	max. 10 bar spray pressure

Technical data

Density (20°C)	pH-value
1,03 kg / l	13,1

Notes

Storage:
Store the product only in the original container and frost-free.
Direct sunlight should be avoided.
After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.