

BÜFA-Oxy AC

Additive for industrial water systems

Properties

- Oxidative odor protection
- for washing systems that work with treated process water
- Can be used without any problems via automatic dosing systems
- Very economical, as it is highly effective

Application

BÜFA-Oxy AC is used as a strong alkaline oxidizing agent wherever acidic products cannot or must not be used. BÜFA-Oxy AC can be continuously added to the process water system as an oxidative odor protection to prevent the development of unpleasant odors.

Dosing

Initial application/use

| | |
|---------------|-------------------------------------|
| Concentration | 100 - 150 ml / m ³ water |
|---------------|-------------------------------------|

Ongoing use

| | |
|---------------|-----------------------------------|
| Concentration | 20 - 40 ml / m ³ water |
|---------------|-----------------------------------|

Technical data

| Density (20°C) | pH-value |
|----------------|-------------|
| 1,20 kg / l | 10,5 - 11,5 |

Notes

Only store the product in the original container and in a frost-free place.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

Complexing agents: The product does not contain any organic complexing agents that are not sufficiently biodegradable, such as EDTA (according to Annex 49 of the Waste Water Ordinance).

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.