

BÜFA-Clean Dry-Active

Additive for the rinse water



Properties

- Neutral, highly effective surfactant combination
- Shortens drying times considerably
- Free from phosphates and solvents
- problem-free applications via automatic dosing systems

Application

BÜFA-Clean Dry-Active is used as a hydrophilic drain dryer after the wash. It is applied via the rinsing arch of the vehicle washing system (washing program - automatic dosing), but can also be applied manually with the last rinsing water. The use of BÜFA-Clean Dry-Active results in the rapid formation of a thin film of water, which causes the water to run off without leaving streaks and supports the drying of the vehicle, especially in car washes without a fan. The formation of limescale and salt stains is prevented. BÜFA-Clean Dry-Active can be mixed with water in any ratio and can be easily applied using automatic dosing systems. If pre-dilution is necessary, follow the instructions of the system and equipment manufacturer.

Manual application: 0.1 - 0.3 % (= 10 - 30 ml / 10 l water)

Vehicle washing system: 0.1 - 0.3 % at the nozzle (depending on the system).

Technical data

Density (20°C)	pH-value
1,01 kg / l	6,50 - 7,50

Notes

Only store the product in the original container and in a frost-free place.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

The surfactants contained in the product meet the conditions regarding biodegradability as specified in Regulation EC 648/2004 for detergents.

The product does not contain any organic complexing agents that are not sufficiently biodegradable, e.g. EDTA (according to Annex 49 of the Waste Water Ordinance).

Due to the formulation components used, no organically bound halogen compounds (AOX) are contained as active substances.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.