

SolventClean SP 1

High-boiling solvent cleaner

Properties

- label-free
- Removes paints of all paint systems highly effectively
- Flash point according to DIN EN 22719-A: ≥ 100 °C

Application

SolventClean SP 1 is a high-boiling solvent-based cleaner. It is suitable for direct use in machine cleaning or manual cleaning, for example of preparation containers or parts. Water-based and solvent-based ink systems are cleaned equally well by SolventClean SP 1 even at room temperature. For particularly thick layers with a high degree of cross-linking of the ink systems to be cleaned, manual spraying of the adhesions and an exposure time of approx. 20 minutes is recommended before machine cleaning.

Suitable surfaces: steel, stainless steel, aluminium, aluminium alloys, galvanized material, non-ferrous metals

Only treat after testing: Plastics

Area of application: manual and machine processes

For removal of: water- and solvent-based paint systems

Technical data

Density (20°C)	pH-value
1,09 kg / l	5 - 6

Cleaning bath

Flashpoint
≥ 100 °C (Pensky-Martens DIN EN 22719-A)

Notes

Store the product in its original container.

Storage should be frost-proof, although the solidified products can be used again after thawing without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.