

## Oldomat OC-Plus

### Machine dishwashing detergent



#### Properties

- chlorine-free
- phosphate-free
- alkaline
- for all degrees water hardness

#### Application

Oldomat OC-Plus is a liquid, non-foaming cleaning concentrate for commercial use in commercial kitchens and other food processing companies. Excellent cleaning results are achieved even with very high water hardness. Dishes made of porcelain, plastic, stainless steel and glass are cleaned gently and residue-free when dosed correctly. Due to the high content of water hardness-binding substances, Oldomat OC-Plus can also be used very well in machines that work without water softening systems; the calcification of appliances and heating elements is effectively prevented. Oldomat OC-Plus is also suitable for use with aluminium at the application concentration! Due to the absence of active chlorine-containing compounds in the product, Oldomat OC-Plus does not contribute to the formation of AOX in waste water. Oldomat OC-Plus is used in commercial dishwashers in industrial kitchens and for cleaning crates, containers and parts in continuous flow systems in food processing plants.

Oldomat OC-Plus is dosed with 1 - 4 g/l water in dishwashers, depending on water hardness and degree of soiling; a concentration of 0.5 - 1 % is recommended in continuous flow systems for food processing.

#### Dosing

##### Dishwashers

|               |  |
|---------------|--|
| Concentration | 1 bis 4 g / l water  |
| Temperature   | gemäß Maschinentakt  |
| Exposure time | gemäß Maschinentakt  |
| Addition      | Oldomat OC-Plus is suitable for use in dishwashers and for items made of stainless steel, plastics, porcelain, glass and aluminum in the usual application concentrations. |

##### Crate washers / continuous flow systems

|               |  |
|---------------|--|
| Concentration | 0,5 - 1,0  |
| Temperature   | gemäß Maschinentakt  |
| Exposure time | gemäß Maschinentakt  |
| Addition      | Oldomat OC-Plus is suitable for use in dishwashers and for items made of stainless steel, plastics, porcelain, glass and aluminum in the usual application concentrations. |

#### Technical data

| Density (20°C) | pH-value          |
|----------------|-------------------|
| 1,28 kg / l    | 12,0 - 13,0 ; 1 % |

### Titration

Prepare 10 ml application solution, fill up with approx. 100 ml distilled water. Titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.

Consumption (ml) x 0.25 = concentration in %

### Notes

Storage:

Store the product only in the original container and frost-free.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.