

SP 1 Gel

Viscous Cleaner

Properties

- label-free
- Suitable for use on light metals and aluminum
- Very strong cleaning effect: removes cross-linked, dried residues of all paint systems, even dried PU paints and inks.
- Gel-like consistency optimized for manual application

Application

SP 1 Gel is a gel-like, solvent-based cleaning agent. It has been specially developed to remove stubborn soiling such as printing inks, resins and polyurethanes. It is safe to use on zinc silicate coatings, light metals and alloys, as well as galvanized material. Due to its gel-like consistency, it remains on the surface to be cleaned for a long time and thus increases the exposure time.

Instructions for use:

Test the material on a non-visible area when using for the first time. Use the product undiluted. Apply to the object to be cleaned, leave to act for some time (do not allow to dry!) and then spray or rinse with plenty of water.

Suitable surfaces: Steel, stainless steel, zinc silicate coatings, light metals and alloys, galvanized material

Only treat after testing: Plastics

Area of application: manual process

For removing: liquid, cross-linked and dried-on adhesions of all paint systems (UV, solvent-based, water-based, 2K). Even very stubborn stains such as PU printing inks/paints (2K paints and varnishes).

Dosing

Concentration	100 %
Temperature	15 °C – 25 °C

Technical data

Density (20°C)	pH-value
1,07 kg / l	5,5

Notes

Only store the product in the original container, tightly closed and dry. After removing partial quantities, please close the container tightly again. Protect from direct sunlight.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.