

SP 1 Gel

Viscous Cleaner

Properties

- No labeling required
- Suitable for use on light metals and aluminum
- Very powerful cleaning action: removes cross-linked, dried residues from all paint systems, including dried PU paints.
- gel-like consistency

Application

SP 1 Gel is a solvent-based, gel-like cleaning agent. It was specially developed to remove stubborn contaminants, such as printing inks, resins, and polyurethanes. It is safe to use on zinc silicate coatings, light metals, and alloys, as well as on galvanized materials. Thanks to its gel-like consistency, it remains on the surface to be cleaned for an extended period, thereby increasing the contact time.

Instructions for Use:

Before first use, test the product on an inconspicuous area. Use the product undiluted. Apply it to the surface to be cleaned, let it sit for a while (do not let it dry!), and then rinse it off with plenty of water.

Suitable surfaces: Steel, stainless steel, zinc silicate coatings, light metals and alloys, galvanized material

Test before use: plastics

Applications: manual application, spray application using compressed air (e.g., paint spray gun)

For removing: liquid, cured, and dried-on residues from all paint systems (UV, solvent-based, water-based, 2K). Even very stubborn contaminants such as PU printing inks/paints (2-component paints and coatings).

Dosing

Concentration	100 %
Temperature	15 °C – 25 °C

Technical data

Density (20°C)	pH-value
1,07 kg / l	5,5

Notes

Only store the product in the original container, tightly closed and dry. After removing partial quantities, please close the container tightly again. Protect from direct sunlight.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.