

Debosan OSM

Acidic crate cleaner / circulation cleaner

Properties

- Fat and protein dissolving
- Removes mineral deposits
- Low-foaming
- compatible with aluminum

Application

Debosan OSM is a strongly acidic wetting agent-containing liquid product based on organic acid with a pronounced cleaning effect against mineral soiling. Thanks to a special combination of active ingredients, it is suitable for circulation and CIP process

Dosing

Pipelines, mixing containers, tanks

| | |
|---------------|-------------|
| Concentration | 0,5 - 1,0 % |
|---------------|-------------|

Technical data

| Density (20°C) | pH-value |
|----------------|-----------------|
| 1,16 | 1,2 - 2,2 ; 1 % |

Titration

Prepare 10 ml application solution and titrate with 0.1 N sodium hydroxide solution against the indicator phenolphthalein.

Consumption (ml) x 0.22 = concentration in %

Notes

Store the product only in the original container and frost-free.
Direct sunlight should be avoided.
After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.