

RHE Spezial

Smoke resin remover



Properties

- highly active wetting agents
- removes protein and grease residues
- very good draining properties and fast dissolving

Application

RHE Spezial is an alkaline spray and basic cleaner for removing heavy soiling from all alkali-resistant surfaces and for cleaning grills and deep fryers. RHE Spezial is used to remove smoke resin deposits in smoke chambers and on smoke trolleys.

Application instructions:

To clean smoke chambers, spray or foam a 5-10% solution onto the walls at approx. 70° C or spray onto an existing automatic cleaning system. Leave the solution to work for 20 - 40 minutes. Avoid drying! To boil out, prepare a solution that fills the volume of the container (1 - 5 %), heat up and leave to act at 60 - 90° C for 15 - 30 minutes. RHE Spezial 2-3% is used to remove stubborn residues. After cleaning, rinse the treated appliances and surfaces thoroughly with water of drinking quality.

Dosing

Smoke resin removal

Concentration	1,0 - 10,0 %
Temperature	60 - 90 °C
Exposure time	abhängig vom Reinigungsverfahren
Addition	After cleaning with RHE Spezial, rinse with drinking water quality.

Technical data

Density (20°C)	pH-value	Conductance (1%; 20°C)
1,33 kg / l	12 - 13 ; 1 %	15,0; 1% mS/cm

Titration

Prepare 10 ml application solution and titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.

Consumption (ml) x 0.15 = concentration in %

Notes

Storage:

Store the product only in the original container and in a frost-free place between +5 and +40°C. Avoid direct sunlight. Please reseal the container tightly after removing partial quantities.

This product is halal certified.

The certification was carried out with reference to the standards "BPJPH Decree No. 20 2023" and "OIC/SMIIC 50-1:2022" in product category K for the production, filling, storage and distribution of cleaning agents and disinfectants.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.