

Status: 12/26/2025

# SolventClean 1018

## Fast evaporating solventbased cleaner

### **Properties**

- fast drying, suitable for EPDM or nitrile rubber rollers.
- Effectively removes residues from all paint systems
- Flash point according to DIN EN 22719-A: 31°C
- designed for cleaning printing plates.

#### **Application**

SolventClean 1018 is a quick-drying solvent cleaner for direct use in manual cleaning. It is classified as a flammable product. The product is excellent for cleaning flexo and offset printing plates, ink pans, anilox rollers and rotary screen cylinders. SolventClean 1018 is also suitable for cleaning EPDM or nitrile rubber rollers. Residues of all ink systems are removed, but it is designed for the removal of UV inks.

#### Instructions for use:

It is possible to mix SolventClean 1018 with alcohol to increase/accelerate the evaporation rate. Test on an inconspicuous area first.

Suitable surfaces: Steel, stainless steel, aluminium, aluminium alloys, galvanized material, non-ferrous

metals

Only treat after testing: Plastics Area of application: manual process

For removing: UV, water-based and solvent-based paint systems

#### **Technical data**

Density (20°C)	pH-value
0,92 kg / I	4 - 7 ; 200 g/l

#### Notes

Only store the product in the original container, tightly closed, in a cool and dry place. After removing partial quantities, please close the container tightly again. Protect from direct sunlight. Do not inhale aerosols, use only in a well-ventilated area.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.