

Status: 3/5/2025

Solvent SafetyClean

High-boiling solvent cleaner

Properties

- Low-emission; flash point according to DIN EN 22719-A: > 80 °C
- For removing solvent-based inks, even when dry; also suitable for cross-linked, water-based inks and **UV** inks
- Suitable for ultrasoniv applications

Application

Solvent SafetyClean is a high-boiling solvent cleaner for direct use in manual cleaning or machine cleaning. Solvent SafetyClean is designed for the removal of paints and varnishes. Solvent SafetyClean can also be used for ultrasonic applications.

Instructions for use:

Cleaned surfaces should be rinsed with water.

Suitable surfaces: Fluorinated polymers, PVDF, PTFF, PP-polypropylene, PE-polyethylene high-density,

EPDM, stainless steel V2A, copper/alloys

Only treat after testing: Aluminum, zinc, steel: corrosion may occur in the presence of water

Not Suitable surfaces: Polyester, PVC: conditionally resistant at 20°C

Application area: manual and machine process

For removal of: solvent-based and UV inks also cross-linked and or in the dried state.

Dosing

Manual Application

Concentration 100 % Temperature 20 °C - 30 °C

Spraying/dipping process

Concentration 100 %

30 °C - 75 °C Temperature

Technical data

Density (20°C)

0,95 kg / I

Cleaning bath

Flashpoint

> 80 °C (Pensky-Martens DIN EN 22719-A)



Status: 3/5/2025

Notes

Store the product in its original container.

Storage should be frost-proof, although the solidified products can be used again after thawing without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.