

# SpeedyClean-S OBG

High-boiling, solvent-based cleaning agent

## Properties

- Low foaming
- Flash point according to DIN EN 22719-A: 63.5 °C
- Suitable for cliché cleaning, all cliché materials

## Application

SpeedyClean-S OBG is a high-boiling solvent cleaner for direct use in automatic plate cleaning. SpeedyClean-S OBG is low foaming and designed for the removal of solvent-based inks and varnishes as well as UV-curing inks. The optimum cleaning parameters to compensate for cleaning bath evaporation and carry-over, refilling with SpeedyClean-S OBG is recommended.

Suitable surfaces: all cliché materials and for surfaces made of ceramic, steel, stainless steel, aluminium, aluminium alloys, galvanized material, non-ferrous metals

Area of application: cliché cleaning machine

For removing: solvent-based printing inks and UV-curing inks

## Dosing

### Plate Cleaning Machine

Concentration	100 %
Temperature	20 °C – 30 °C

## Technical data

### Density (20°C)

0,95

## Notes

Store the product in its original container.

Storage should be frost-proof, although the solidified products can be used again after thawing without any loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.