


Powerclean Quick

Special instant cleaner

Properties

- universally applicable
- extremely effective against persistent dirt
- oil and grease emulsifying
- can be used on alkali-resistant and wipeable surfaces



Application

Powerclean Quick is an aluminum-compatible and highly effective special instant cleaner for all washable surfaces. Thanks to the perfectly balanced mixture of well wetting surfactants with grease and oil emulsifying surfactants, Powerclean Quick cleans powerfully and is nevertheless very gentle on materials. Even persistent dirt is removed quickly and thoroughly. The cleaned surfaces regain their original appearance and shine. Aluminum surfaces can also be treated with Powerclean Quick. Powerclean Quick does not contain EDTA or NTA. Powerclean Quick can be used, for example, in industry, catering, commercial kitchens, agriculture, building cleaning, vehicle fleet maintenance and car workshops. Powerclean Quick is diluted with water and sprayed onto the surface or applied with a brush or sponge. After sufficient contact time, wipe with a damp cloth or rinse with clear water.

The use of warm water improves the cleaning result. Ensure material compatibility when using for the first time.

Dosing

Maintenance cleaning

Concentration	1:5 bis 1:50 in relation to water
Addition	For problematic soiling, use a more concentrated, higher dosage.

Technical data

Density (20°C)	pH-value
1,02 kg / l	10,5 ; 1 %

Titration

Prepare 10 ml application solution and titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.

Consumption (ml) x 3.76 = concentration in %

Notes

Storage:
Store the product only in the original container and in a frost-free place.
Direct sunlight should be avoided.
The container should be resealed after partial quantities have been removed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.